## www.kayakzebec.com Tel: 0818966017 Line ID: 66818966017 E-mail: ifo@gr.co.th





## เครื่องยนต์ติดท้ายเรือ ชูชูกิ 15 แรงม้า แบบ 2 จังหวะ

## **Item specifications**

Maximum output	15 HP
Number of cylinders	2
Engine type	2-stroke
Starting system	Manual
Steering	Tiller
Trim method	Manual trim and tilt
Piston displacement, cm <sup>3</sup>	284
Piston displacement, in <sup>3</sup>	17.3
Bore x Stroke, mm/mm	59 x 52
Bore x Stroke, in/in	2.32 x 2.04
Fuel delivery system	Carburetor
Alternator	12V 6A (optionally)**
Gear ratio	1.92:1
Gear ratio Gear shift	F-N-R
Equipped pro or the re	3x9-1/4x9
Prone Ling Cation	Regular (Right-hand)
Prepeller selection (pitch)*	7-11 "
ruel tank capacity, L	25
Fuel tank capacity, US gal	6.6
Lubricating system	Pre-mixing
Full trottle operating range	4800 - 5600
Ignition system	Pointless electronic ignition
NGK spark plug	BR7HS-10
Recommended transom height, mm	381
Recommended transom height, in	15
Lower unit gear oil capacity, ml	250
Lower unit gear oil capacity, fl oz	8.45
Dry Weight (including battery cable, not including propeller and engine oil), kg	33
Dry Weight (including battery cable, not including propeller and engine oil), lbs	72.7
Exhaust	Through prop hub exhaust
Drive protection	Rubber hub
Manufacturer	Suzuki

