www.kayakzebec.com Tel: 0818966017 Line ID: 66818966017 E-mail: ifo@gr.co.th



เครื่องยนต์ติดท้ายเรือ ชูซูกิ 40 แรงม้า แบบ 2 จังหวะ

Item specifications

item specifications	
Maximum output	40 HP
Number of cylinders	2
Engine type	2-stroke
Starting system SUZUKI	Manual
Steering 40	Tiller
Trim method	Ma. wal trim and tilt
Piston displacement, cm ³	696
Piston displacement, in ³	42.5
Bore x Stroke, mm/mm	79 x 71
Bore x Stroke, in/in	3.11 x 2.79
Fuel delivery system	Carburetor
Alternator	12V 6A
Gear ratio	2.09:1
Gear shift	F-N-R
Equipped propeller*	3x11-1/2x13
Propeller rotation	Regular (Right-hand)
Propeller selection (pitch)*	9-16 "
Fuel tank capacity, L	25
Fuel tank capacity, US gal	6.6
Lubricating system	Pre-mixing
Full trottle operating range	5000 - 5600
Ignition system	Pointless electronic ignition
NGK spark plug	BR8HS
Recommended transom height, mm	508
Recommended transom height, in	20
Lower unit gear oil capacity, ml	610
Lower unit gear oil capacity, fl oz	20.62
Dry Weight (including battery cable, not including propeller and engine oil), kg	75
Dry Weight (including battery cable, not including propeller and engine oil), lbs	165.3
Exhaust	Through prop hub exhaust
Drive protection	Rubber hub
Manufacturer	Suzuki